Surgical Gowns

Fabric-Reinforced



	CODE	DESCRIPTION	SIZE	CASE QTY	CASE DIMENSIONS
N	V90-2310	Surgical Gown, Fabric-Reinforced	M	44	18x15x12" (46x38x29.5cm)
S	V90-2310-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	M	26	18x12x19" (46x30x49cm)
N	V90-2320	Surgical Gown, Fabric-Reinforced	L	44	20x14x12" (51x41x30cm)
S	V90-2320-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	L	26	18x12x19" (46x30x49cm)
N	V90-2321	Surgical Gown, Fabric-Reinforced	L, X-Long	44	20x14x12" (51x41x30cm)
S	V90-2321-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	L, X-Long	26	18x12x19" (46x30x49cm)
N	V90-2330	Surgical Gown, Fabric-Reinforced	XL	44	20x14x12" (51x41x30cm)
S	V90-2330-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	XL	24	18x12x19" (46x30x49cm)
N	V90-2331	Surgical Gown, Fabric-Reinforced	XL, X-Long	44	20x14x12" (51x41x30cm)
S	V90-2331-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	XL, X-Long	24	18x12x19" (46x30x49cm)
N	V90-2340	Surgical Gown, Fabric-Reinforced	2XL	36	20x14x12" (51x41x30cm)
S	V90-2340-S2	Surgical Gown, Fabric-Reinforced, 2 Hand Towels	2XL	24	18x12x19" (46x30x49cm)

Materials

 Multilayered SMS Material with Antistatic Properties and Alcohol Repellency

Product Attributes

- · Adjustable hook and loop fenestration
- Knit cuffs
- · Set-in sleeves
- · Sonically seamed on all construction points

Sterilization

Sterile: Sterilized by EO (ethylene oxide). Product is sterile unless the package has been damaged or opened.

Non-Sterile: If a product is delivered non-sterile and is ultimately for use in sterile environments, it is intended to be sterilized by the repackager. This includes further packaging and sterilization according to the validated processes of the re-packager. These products are to be sterilized by ethylene oxide (EO). Other methods of sterilization have not been validated by Alleset.

Shelf Life

Sterile: 5 years

Non-Sterile: Established at 5 years based upon sterile packaged product aging studies and normal warehouse storage conditions. After 5 years, the product should be performance tested to ensure compliance to specifications.

Product Certifications/Standards


- ANSI/AAMI PB70:2012 Level 3 Liquid Barrier Protection
- EN13795:2011 Standard Performance
- Sterile: CE certified as Class I, according to MDD93/42/EEC Annex IX, Rule 4
- Non-Sterile: CE certified as Class I, according to MDR 2017/745, Annex VIII, Rule

Manufacturing Certifications/ Registrations

• EN ISO 13485:2016

Storage

· General warehouse conditions



Code	A: Back Length	B: Sleeve Length	C: Body Reinf. Top Width	D: Body Reinf. Bottom Width	E: Body Reinf. Height
V90-2310 (S2/NS)	41" (104cm)	23" (58cm)	12" (30cm)	17" (43cm)	22" (56cm)
V90-2320 (S2/NS)	45" (115cm)	24" (62cm)	13" (33cm)	17" (43cm)	25" (64cm)
V90-2321 (S2/NS)	54" (138cm)	24" (62cm)	13" (33cm)	17" (43cm)	25" (64cm)
V90-2330 (S2/NS)	49" (124cm)	25" (64cm)	13" (33cm)	17" (43cm)	28" (71cm)
V90-2331 (S2/NS)	58" (147cm)	25" (64cm)	13" (33cm)	17" (43cm)	28" (71cm)
V90-2340 (S2/NS)	51" (130cm)	30" (75cm)	16" (41cm)	21" (53cm)	30" (76cm)
Tolerance	±0.8" (2cm)	±0.4" (1cm)	±0.4" (1cm)	±0.4" (1cm)	±0.8" (2cm)













Alleset
4142 Industry Way
Flowery Branch, GA 30542,
USA
www.alleset.com
SM-TDS-002 2022
Country of Origin Abbreviations per ISO 3166-1, Alpha-2 Codes.



GRI Medical & Electronic Technology Co., LTD 1805 Honggao Road, 314031 Jiaxing, Zhejiang PEOPLE'S REPUBLIC OF CHINA www.alleset.com US FDA Establishment Registration #3004911384



Emergo Europe B.V. Prinsessegracht 20 2514 AP The Hague The Netherlands www.emergobyul.com

A GRI COMPANY

