# **Surgical Gowns**

# Film-Reinforced



	CODE	DESCRIPTION	SIZE	CASE QTY	CASE DIMENSIONS
N	V90-4210	Surgical Gown, Film-Reinforced	M	36	19x16x12.5" (50x42x32cm)
S	V90-4210-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	М	26	18x12x19" (46x30x49cm)
N	V90-4220	Surgical Gown, Film-Reinforced	L	36	19x16x12.5" (50x42x32cm)
S	V90-4220-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	L	26	18x12x19" (46x30x49cm)
N	V90-4221	Surgical Gown, Film-Reinforced	L, X-Long	36	19x16x12.5" (50x42x32cm)
S	V90-4221-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	L, X-Long	26	18x12x22" (46x30x55cm)
N	V90-4230	Surgical Gown, Film-Reinforced	XL	36	19x16x12.5" (50x42x32cm)
S	V90-4230-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	XL	24	18x12x19" (46x30x49cm)
N	V90-4231	Surgical Gown, Film-Reinforced	XL, X-Long	36	19x16x12.5" (50x42x32cm)
S	V90-4231-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	XL, X-Long	24	18x12x22" (46x30x55cm)
N	V90-4240	Surgical Gown, Film-Reinforced	2XL	28	19x16x12.5" (50x42x32cm)
S	V90-4240-S2	Surgical Gown, Film-Reinforced, 2 Hand Towels	2XL	24	18x12x19" (46x30x49cm)

#### **Materials**

- Multilayered SMS Material with Antistatic Properties and Alcohol Repellency
- Non-Woven Polypropylene (PP) and Polyethylene (PE) Film

### **Product Attributes**

- · Adjustable hook and loop fenestration
- · Knit cuffs
- · Set-in sleeves
- · Sonically seamed on all construction points

## Sterilization

Sterile: Sterilized by EO (ethylene oxide). Product is sterile unless the package has been damaged or opened.

Non-Sterile: If a product is delivered non-sterile and is ultimately for use in sterile environments, it is intended to be sterilized by the repackager. This includes further packaging and sterilization according to the validated processes of the re-packager. These products are to be sterilized by ethylene oxide (EO). Other methods of sterilization have not been validated by Alleset.

#### **Shelf Life**

Sterile: 5 years

Non-Sterile: Established at 5 years based upon sterile packaged product aging studies and normal warehouse storage conditions. After 5 years, the product should be performance tested to ensure compliance to specifications.

# **Product Certifications/Standards**


- ANSI/AAMI PB70:2012 Level 3 Liquid Barrier Protection
- EN13795:2011 High Performance
- · Sterile: CE certified as Class I, according to MDD93/42/EEC Annex IX, Rule 4
- · Non-Sterile: CE certified as Class I, according to MDR 2017/745, Annex VIII, Rule

# **Manufacturing Certifications/ Registrations**

• EN ISO 13485:2016

#### Storage

· General warehouse conditions



Code	A: Back Length	B: Sleeve Length	C: Body Reinf. Top Width	D: Body Reinf. Bottom Width	E: Body Reinf. Height
V90-4210 (S2/NS)	41" (104cm)	23" (58cm)	12" (30cm)	17" (43cm)	22" (56cm)
V90-4220 (S2/NS)	45" (115cm)	24" (62cm)	13" (33cm)	17" (43cm)	25" (64cm)
V90-4221 (S2/NS)	54" (138cm)	24" (62cm)	13" (33cm)	17" (43cm)	25" (64cm)
V90-4230 (S2/NS)	49" (124cm)	25" (64cm)	13" (33cm)	17" (43cm)	28" (71cm)
V90-4231 (S2/NS)	58" (147cm)	25" (64cm)	13" (33cm)	17" (43cm)	28" (71cm)
V90-4240 (S2/NS)	51" (130cm)	30" (75cm)	16" (41cm)	21" (53cm)	30" (76cm)
Tolerance	±0.8" (2cm)	±0.4" (1cm)	±0.4" (1cm)	±0.4" (1cm)	±0.8" (2cm)















www.alleset.com

SM-TDS-002 2022

Country of Origin Abbreviations per ISO 3166-1, Alpha-2 Codes.



GRI Medical & Electronic Technology Co., LTD 1805 Honggao Road, 314031 Jiaxing, Zhejiang PEOPLE'S REPUBLIC OF CHINA www.alleset.com US FDA Establishment Registration #3004911384



Emergo Europe B.V. Prinsessegracht 20 2514 AP The Hague The Netherlands www.emergobyul.com

